

CLAIMS

What is claimed is:

1 1. A method of selecting one of a plurality of queues for service, at least one of the plurality of
2 queues associated with a first traffic class, the method comprising the steps of:

3 (a) identifying each first traffic class (FTC) queue having at least one enqueued cell as an occupied
4 FTC queue wherein at least one FTC queue is provisioned for burst scheduling of multiple cells when
5 serviced;

6 (b) identifying an occupied FTC queue provisioned for burst scheduling as a super-occupied FTC
7 queue when the number of cells enqueued is greater than a specified number;

8 (c) setting as eligible for service each occupied FTC queue based on a FTC scheduling
9 algorithm; and

10 (d) selecting for service an eligible FTC queue based on a corresponding sub-priority of each
11 eligible FTC queue, wherein:

12 each FTC queue is assigned a sub-priority based on a service level of a connection associated with
13 enqueued cells; and

14 when the super-occupied queue is serviced, the number of cells dequeued is based on a burst size.

1 2. The invention of claim 1, wherein, for step (a) the first traffic class comprises traffic
2 having a provisioned guaranteed level of service.

1 3. The invention of claim 2, wherein, for step (a) the provisioned guaranteed level of service
2 is a either a guaranteed bandwidth or a guaranteed effective bandwidth.

1 4. The invention of claim 1, wherein step (a) comprises the steps of:

2 (a1) identifying whether a queue having cells associated with unicast traffic is occupied; and

3 (a2) identifying whether a queue having cells associated with multicast traffic is occupied.

1 5. The invention of claim 1, wherein, for step (b), the FTC scheduling algorithm is a shaped
2 virtual clock algorithm.

1 6. The invention of claim 5, wherein, for step (c), each FTC queue has a corresponding down
2 counter and service period value, wherein step (c) further comprises the steps of, during a scheduling

interval, counting down from the service period value to a predefined value, and setting the corresponding FTC queue as eligible when the down counter reaches the predefined value.

7. The invention of claim 6, wherein step (c) further comprises the step of continuing to count from the predefined value to generate a service delay value, and for a subsequent scheduling interval adjusting the service period value based on the service delay value.

8. The invention of claim 1, wherein step (c) further comprises the step of further setting an occupied FTC queue as eligible based on congestion information.

9. The invention of claim 1, wherein step (d) comprises the step of, for each sub-priority, addressing with a pointer the FTC queue having the highest priority value within those eligible FTC queues assigned to the sub-priority, the sub-priority of an eligible FTC queue based on when the order in which the eligible FTC queue is set as eligible.

10. The invention of claim 9, further comprising the steps of: ranking each sub-priority, selecting the FTC queue within a sub-queue based on the pointer, and selecting for service the selected FTC queue from among the sub-queues based on the corresponding sub-queue's rank.

11. The invention of claim 9, further comprising the steps of generating a bid when the FTC queue selector selects a given FTC queue for service, and servicing the given FTC queue when the bid is granted.

12. The invention of claim 1, wherein at least one of the plurality of queues is associated with a second traffic class (STC), step (a) further comprises the step of identifying each STC queue having at least one enqueued cell as an occupied STC queue, and the method further comprises the steps of:

(e) setting as eligible for service each occupied STC queue for based on a STC scheduling algorithm;

(f) STC queue selector configured to select for service an eligible STC queue based on the corresponding priority of the eligible STC queue; and

(g) scheduler /arbiter controller configured to select one of the FTC queue selected for service, if present, and the STC queue selected for service, if present.

13. The invention of claim 12, further comprising the steps of assigning each FTC queue priority over each STC queue, and selecting either the FTC queue or the STC queue based on the assigned priority.

1 14. The invention of claim 12, wherein, for step (e), the STC scheduling algorithm is a
2 weighted round robin scheduling algorithm.

1 15. The invention of claim 12, wherein step (e) includes the step of accounting for delay in
2 service of each eligible STC queue.

1 16. The invention of claim 12, for step (e), the second traffic class is best effort traffic.

1 17. The invention of claim 1, wherein the method is embodied as program steps in a processor
2 of an integrated circuit.

1 18. A scheduler for selecting one of a plurality of queues for service, at least one of the
2 plurality of queues associated with a first traffic class (FTC), the scheduler comprising:

3 an occupancy processor configured to identify each FTC queue having at least one enqueued cell
4 as an occupied FTC queue, wherein:

5 1) at least one FTC queue may be provisioned for burst scheduling of multiple
6 cells when serviced, and

7 2) an occupied FTC queue provisioned for burst scheduling is also identified as a
8 super-occupied FTC queue when a number of cells enqueued is greater than a provisioned
9 number;

10 a FTC eligibility processor configured to set as eligible for service each occupied FTC queue
11 based on a FTC scheduling algorithm; and

12 a FTC queue selector configured to select for service an eligible FTC queue,

13 wherein each FTC queue is assigned a sub-priority based on a service level of a connection
14 associated with enqueued cells, the FTC queue selector selects an eligible FTC queue based on the
15 corresponding sub-priority of each eligible FTC queue, and when the super-occupied FTC queue is
16 serviced, the number of cells dequeued is based on a burst size.

1 19. The invention of claim 18, wherein the first traffic class comprises traffic having a
2 provisioned guaranteed level of service.

1 20. The invention of claim 19, wherein the provisioned guaranteed level of service is either a
2 guaranteed bandwidth or a guaranteed effective bandwidth.

1 21. The invention of claim 18, wherein the occupancy processor comprises:

2 a unicast occupancy processor configured to identify whether a queue having cells associated with
3 unicast traffic is occupied; and

4 a multicast occupancy processor configured to identify whether a queue having cells associated
5 with multicast traffic is occupied.

1 22. The invention of claim 18, wherein the FTC scheduling algorithm is a shaped virtual clock
2 algorithm.

1 23. The invention of claim 22, wherein the FTC eligibility processor comprises a plurality of
2 down counters, each FTC queue having a corresponding down counter and service period value, wherein
3 during a scheduling interval each down counter counts from the service period value to a predefined value,
4 and the corresponding FTC queue is set as eligible when the down counter reaches the predefined value.

1 24. The invention of claim 23, wherein, the down counter continues to count from the
2 predefined value to generate a service delay value, wherein for a subsequent scheduling interval the service
3 period value is adjusted based on the service delay value.

1 25. The invention of claim 18, wherein the FTC eligibility processor receives output port
2 congestion information, and the FTC eligibility processor sets an occupied FTC queue as eligible based on
3 the congestion information.

1 26. The invention of claim 18, wherein, for each sub-priority, the FTC queue selector
2 comprises a pointer addressing the FTC queue having the highest priority value within those eligible FTC
3 queues assigned to the sub-priority, the priority of an eligible FTC queue based on when the order in which
4 the eligible FTC queue is set as eligible by the FTC eligibility processor.

1 27. The invention of claim 26, wherein each sub-priority is ranked, and the FTC queue
2 selector selects the FTC queue within a sub-queue based on the pointer, and selects for service the selected
3 FTC queue from among the sub-queues based on the corresponding sub-queue's rank.

1 28. The invention of claim 26, wherein, when the FTC queue selector selects a given FTC
2 queue for service, a bid is generated and the given FTC queue is serviced when the bid is granted.

1 29. The invention of claim 18, wherein at least one of the plurality of queues is associated with
2 a second traffic class (STC), the occupancy processor is configured to identify each STC queue having at
3 least one enqueued cell as an occupied STC queue, and the scheduler further comprises:

4 a STC eligibility processor configured to set as eligible for service each occupied STC queue for
5 based on a STC scheduling algorithm;

6 a STC queue selector configured to select for service an eligible STC queue based on the
7 corresponding priority of the eligible STC queue; and

8 a scheduler /arbiter controller configured to select one of the FTC queue selected for service, if
9 present, and the STC queue selected for service, if present.

1 30. The invention of claim 29, wherein each FTC queue is assigned priority over each STC
2 queue, and the scheduler/arbiter controller selects either the FTC queue or the STC queue based on the
3 assigned priority.

1 31. The invention of claim 29, wherein the STC scheduling algorithm is a weighted round
2 robin scheduling algorithm.

1 32. The invention of claim 29, wherein the STC scheduling algorithm accounts for delay in
2 service of each eligible STC queue.

1 33. The invention of claim 29, wherein the second traffic class is best effort traffic.

1 34. The invention of claim 18, wherein the scheduler is embodied in a telecommunications
2 switch.

1 35. The invention of claim 34, wherein the telecommunications switch is a three stage switch,
2 the plurality of queues are associated with connections received at a plurality of input ports of the first
3 stage, and the scheduler is embodied in the first stage to transfer cells to a plurality of input links of the
4 second stage.

1 36. The invention of claim 35, wherein the telecommunications switch is a three stage switch,
2 the plurality of queues are associated with cells received from output links of the second stage, and the
3 scheduler is embodied in the third stage to transfer cells from the plurality of queues to a plurality of output
4 ports.

1 37. The invention of claim 18, wherein the scheduler is embodied in an integrated circuit.

1 38. A computer-readable medium having stored thereon a plurality of instructions, the plurality
2 of instructions including instructions which, when executed by a processor, cause the processor to
3 implement a method of selecting one of a plurality of queues for service, at least one of the plurality of
4 queues associated with a first traffic class, the method comprising the steps of:

5 (a) identifying each first traffic class (FTC) queue having at least one enqueued cell as an occupied
6 FTC queue wherein at least one FTC queue is provisioned for burst scheduling of multiple cells when
7 serviced;

8 (b) identifying an occupied FTC queue provisioned for burst scheduling as a super-occupied FTC
9 queue when the number of cells enqueued is greater than a specified number;

10 (c) setting as eligible for service each occupied FTC queue based on a FTC scheduling
11 algorithm; and

12 (d) selecting for service an eligible FTC queue based on a corresponding sub-priority of each
13 eligible FTC queue, wherein:

14 each FTC queue is assigned a sub-priority based on a service level of a connection associated with
15 enqueued cells; and

16 when the super-occupied queue is serviced, the number of cells dequeued is based on a burst size.

01
02
03
04
05
06
07
08
09
10
11
12
13
14
15
16